

**FEATURES**

- ◆ Access over IP & analogous telephone line ( modem needed )
- ◆ Full control under any OS, in BIOS mode , during boot, at Blue Screen
- ◆ Switch mode: Hot key & OSD menu control
- ◆ 256 bit SSL encryption of all transmitted data & certificate management
- ◆ Port to connect a user console for direct analogous access to KVM switch
- ◆ Host computer can manage up to 1024 computers
- ◆ Support OS: Windows, Linux, Unix

**Specification**

GENERAL DATA	
Series	YHK1702C
No.for direct connection of PC	8 / 16 / 32
Max.No.for connection of PC	256 / 512 / 1024
Connection port	CAT 5
OSD switching	Support
Switch mode	Hot key & OSD menu
Switch scan time	1-255s ( OSD adjustable )
Display control	multi-language OSD menu control
Keyboard / mouse	104 mechanical keyboard / touch pad
Display	
Type	TFT LCD
Size	17 inch
Resolution	1280 x 1024
Color display	16.7 M
Brightness	300 cd/m <sup>2</sup>
Contrast ratio	700 : 1
Backlight	CCFL LED
Pixel distance	0.294 ( H ) x 0.294 ( W ) mm
LCD MTBF	> 50,000H
Power supply	
Voltage input	AC100 - 240V, support hotplug, 35W
MTBF	> 10,0000H ( 25℃ )
Environmental	
Operating temperature	-10 - 60 ℃
Storage temperature	-30 - 70 ℃
Physical characteristic	
Gross weight	17 KG ~ 22.5 KG
Relative humidity	5% - 95% @ 40℃ , no condensing
Vibration	5-17Hz
Material	Steel
Color	Black
Dimension ( W x H x D )	568 x 480 x 44 mm
Suitable cabinet dimension	800 ~ 1040 mm
Working life	120,000 H
Certificate	
FCC	Yes
CE	Yes
CCC	Yes

**Order information**

IP KVM - 1708C	1U rack mount 17" TFT LED KVM drawer with 8 port over IP
IP KVM - 1716C	1U rack mount 17" TFT LED KVM drawer with 16 port over IP
IP KVM - 1732C	1U rack mount 17" TFT LED KVM drawer with 32 port over IP