



**FEATURES**

- ◆LED display / touchpad mouse /104 keyboard with digital zone /E-switch
- ◆Resolution: 1280\*1024 @ 75HZ ( Max )
- ◆Switch mode: Hot key & OSD control
- ◆Supporting DDC2B; automatically detect the screen model
- ◆Humanized withdrawing installation design for rack space
- ◆Support OS: Windows, Linux, Unix

**Specification**

GENERAL DATA	
Series	YHK1901
No.for direct connection of PC	1
Max.No.for connection of PC	1
Connection port	D-SUB15 port ( LCD, USB / PSII / USB & PSII keyboard, mouse )
OSD switching	Support
Switch mode	Hot key & OSD menu
Switch scan time	1-255s ( OSD adjustable )
Display control	multi-language OSD menu control
Keyboard / mouse	104 mechanical keyboard / touch pad
Display	
Type	TFT LCD
Size	19"
Resolution	1280 x 1024
Color display	16.7 M
Brightness	300 cd/m2
Contrast ratio	700 : 1
Backlight	CCFL LED
Pixel distance	0.294 ( H ) x 0.294 ( W ) mm
LCD MTBF	> 50,000H
Power supply	
Voltage input	AC100 - 240V, support hotplug, 35W
MTBF	> 10,0000H ( 25℃ )
Environmental	
Operating temperature	-10 - 60 °C
Storage temperature	-30 - 70 °C
Physical characteristic	
Gross weight	20 KG
Relative humidity	5% - 95%@40℃ , no condensing
Vibration	5-17Hz
Material	Steel
Color	Black
Dimension ( W x H x D )	586 x 480 x 44 mm
Suitable cabinet dimension	800 ~ 1040 mm
Working life	120,000 H
Certificate	
FCC	Yes
CE	Yes
CCC	Yes

**Order information**

KVM - 1901U	1U rack mount 17" TFT LCD W / 1 port KVM switch, W / 12V power supply, W / USB cable
KVM - 1901P	1U rack mount 17" TFT LCD W / 1 port KVM switch, W / 12V power supply, W / PSII cable
KVM - 1901M	1U rack mount 17" TFT LCD W / 1 port KVM switch, W / 12V power supply, W / PSII & USB cable