

**FEATURES**

- ◆19" 1U rack mount LED KVM switch with touch pad & mouse
- ◆Resolution: 1280 x 1024; Brightness: 300cd/m²
- ◆Switch mode: Hot key & OSD control
- ◆Support USB + PS2 local console
- ◆Humanized withdrawing installation design for rack space
- ◆Support OS: Windows, Linux, Unix

Specification

GENERAL DATA	
Series	YHK1902
No.for direct connection of PC	4 / 8 / 16
Max.No.for connection of PC	128 / 256 / 512
Connection port	D-SUB15 port (LCD, USB / PSII / USB & PSII keyboard, mouse)
OSD switching	Support
Switch mode	Hot key & OSD menu
Switch scan time	1-255s (OSD adjustable)
Display control	multi-language OSD menu control
Keyboard / mouse	104 mechanical keyboard / touch pad
Display	
Type	TFT LCD
Size	19"
Resolution	1280 x 1024
Color display	16.7 M
Brightness	300 cd/m ²
Contrast ratio	700 : 1
Backlight	CCFL LED
Pixel distance	0.294 (H) x 0.294 (W) mm
LCD MTBF	> 50,000H
Power supply	
Voltage input	AC100 - 240V, support hotplug, 35W
MTBF	> 10,000H (25 °C)
Environmental	
Operating temperature	-10 - 60 °C
Storage temperature	-30 - 70 °C
Physical characteristic	
Gross weight	17 KG ~ 22.5 KG
Relative humidity	5% - 95%@40°C , no condensing
Vibration	5-17Hz
Material	Steel
Color	Black
Dimension (W x H x D)	610 x 480 x 44 mm
Suitable cabinet dimension	800 ~ 1040 mm
Working life	120,000 H
Certificate	
FCC	Yes
CE	Yes
CCC	Yes

Order information

IP KVM - 1904M	1U rack mount 19" TFT LCD KVM switch, W / keyboard & touchpad, W / 4 port VGA, W / 12V power supply, W / USB cable
IP KVM - 1908M	1U rack mount 19" TFT LCD KVM switch, W / keyboard & touchpad, W / 8 port VGA, W / 12V power supply, W / USB cable
IP KVM - 1916M	1U rack mount 19" TFT LCD KVM switch, W / keyboard & touchpad, W / 16 port VGA, W / 12V power supply, W / USB cable